BUS AIR CONDITION SYSTEM

2007 NEW DESIGN



SYTSTEM TYPE	APPLICATION	COOLING CAPACITY
PAC12AH	66.5m BUS	12000-14000Kcal/h
PAC14DH	66.5m BUS	14000-16000Kcal/h
PAC16AH	77.6m BUS	14000-16000Kcal/h
PAC16DH-2	6.5-7.5m BUS	15000-16000Kcal/h
PAC18B1	7.9-8.3m BUS	16000-18000Kcal/h
PAC22B1	10-11m BUS	21000-22000Kcal/h
PAC28B1	10-11m BUS	26000-28000Kcal/h
PAC32B1	11-12m BUS	28000-32000Kcal/h

OEM SUPPLIER

Bus Air-Condition System PAC12AH:





NO.	1	ΓERM	TECHNICAL SPECIFICATIONS	NOTES
1	System Type		PAC12AH	
2	Model		Built-in	
3	Cooling Capacity		12000~14000Kcal/h	
4	Applications		6~6.5m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V-12V	PAERMA Compressor
		Туре	Swash Plate	
		Displacement	313.4cc/rev	
6	Compressors	Power Consumption	7.5KW	
		Lubricant	ZXL 100PG 600ml	
		Weight	14.5KG (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	3400m3/h	
7	0	Number of Fans	2	Made in China / Made in Japan
7	Condenser Unit	Filter Drier	3A Grade	Made in China
		High Pressure Switch	HP:32kgf/cm2 , LP:2kgf/ cm2	Made in China
		Weight	26KG	
		Size (mm)	960 X 430 X 348	
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	2550 m3/h	
8	Evaporator Unit	Number of Blowers	3	
		Expansion Valve	3.0RT	Japan Denso
		Weight	20KG	
		Size (mm)	1320 X 500 X 170	
		Current Consumption	35A/24VDC or 70A/12VDC	
		Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
11	Accessories	Pulley		Made in Koera
	D (1)	Regulator	201	Made in China
12	Refrigeration		R134a	Consumer Provide

Bus Air-Condition System PAC14DH:





NO.		TERM	TECHNICAL SPECIFICATIONS	NOTES
1	System Type		PAC14DH	
2	Model		Condenser Unit is Roof Mounting	
3	Cooling Capacity		14000~16000Kcal/h	
4	Applications		6~6.5m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V-12V	PAERMA Compressor
		Туре	Swash Plate	
		Displacement	313.4cc/rev	
6	Compressors	Power Consumption	7.5KW	
		Lubricant	ZXL 100PG 600ml	
		Weight	14.5KG (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	5400m3/h	
7	Condenser Unit	Number of Fans	3	Made in China / Made in Japan
/	Condenser Unit	Filter Drier	3A Grade	Made in China
		High Pressure Switch	HP:32kgf/cm2 , LP:2kgf/ cm2	Made in China
		Weight	33KG	
		Size (mm)	1755 X 1450 X 180	
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	3200 m3/h	
8	Evaporator Unit	Number of Blowers	3	
	•	Expansion Valve	3.0RT	Japan Denso
		Weight	36KG	
		Size (mm)	1320 X 500 X 170	
		Current Consumption	35A/24VDC or 70A/12VDC	
		Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
11		Pulley		Made in Koera
	Regulator			Made in China
12	Refrigeration		R134a	Consumer Provide

Bus Air-Condition System PAC16AH:





NO.		TERM .	TECHNICAL SPECIFICATIONS	NOTES
1	System Type		PAC16AH	
2	Model		Built-in	
3	Cooling Capacity		14000~16000Kcal/h	
4	Applications		7~7.6m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V-12V	PAERMA Compressor
		Туре	Swash Plate	
		Displacement	313.4cc/rev	
6	Compressors	Power Consumption	7.5KW	
		Lubricant	ZXL 100PG 600ml	
		Weight	14.5KG (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	5100m3/h	
7	0	Number of Fans	3	Made in China / Made in Japan
7	Condenser Unit	Filter Drier	3A Grade	Made in China
		High Pressure Switch	HP:32kgf/cm2 , LP:2kgf/ cm2	Made in China
		Weight	33KG	
		Size (mm)	1090 X 410 X 360	
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	4200 m3/h	
8	Evaporator Unit	Number of Blowers	4	
	.,	Expansion Valve	3.0RT	Japan Denso
		Weight	36KG	
		Size (mm)	1700 X 500 X 140	
		Current Consumption	35A/24VDC or 70A/12VDC	
		Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
11	Accessories	Pulley		Made in Koera
		Regulator		Made in China
12	Refrigeration		R134a	Consumer Provide

Bus Air-Condition System PAC16DH-2





NO.	1	TERM .	TECHNICAL SPECIFICATIONS	NOTES
1	System Type		PAC16DH-2	
2	Model		Condenser Unit is Roof Mounting	
3	Cooling Capacity		15000~16000Kcal/h	
4	Applications		6.5~7.5m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V-12V	PAERMA Compressor
		Туре	Swash Plate	
		Displacement	313.4cc/rev	
6	Compressors	Power Consumption	7.5KW	
		Lubricant	ZXL 100PG 600ml	
		Weight	14.5KG (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	6400m3/h	
7	One day and black	Number of Fans	4	Made in China / Made in Japan
7	Condenser Unit	Filter Drier	3A Grade	Made in China
		High Pressure Switch	HP:32kgf/cm2 , LP:2kgf/ cm2	Made in China
		Weight	33KG	
		Size (mm)	2295 X 1445 X 180	
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	5250 m3/h	
8	Evaporator Unit	Number of Blowers	4	
	.,	Expansion Valve	3.0RT	Japan Denso
		Weight	36KG	-
		Size (mm)	1700 X 500 X 170	
		Current Consumption	35A/24VDC or 70A/12VDC	
0	Electrical Control	Thermo Start	Mainly Parts Import	Made in China
Э	LIBOUILGI COITUU	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
	Accessories	Pulley		Made in Koera
	Regulator		D404	Made in China
12	Refrigeration		R134a	Consumer Provide

Bus Air-Condition System PAC18B1





NO.		TERM .	TECHNICAL SPECIFICATIONS	NOTES
1	System Type		PAC18B 1	
2	Model		Roof Mounting	
3	Cooling Capacity		16000~18000Kcal/h	
4	Applications		7.9~8.3m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V-12V	PAERMA Compressor
		Туре	Swash Plate	
_		Displacement	313.4cc/rev	
6	Compressors	Power Consumption	7.5KW	
		Lubricant	ZXL 100PG 600ml	
		Weight	14.5KG (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	5550m3/h	
7	0	Number of Fans		Made in China / Made in Japan
7	Condenser Unit	Filter Drier	3A Grade X 2	Made in China
		High Pressure Switch	OFF: 24.5kgf/cm2 , ON:17kgf/ cm2	Made in China
		Low Pressure Switch	OFF: 0.8kgf/cm2 , ON:2.2kgf/ cm2	
		Size (mm)		
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	4200 m3/h	
8	Evaporator Unit	Number of Blowers	4	
		Expansion Valve	6.0RT	Japan Denso
		Weight		
		Size (mm)		
		, ,	64A/24VDC or 128A/12VDC	
		Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System	•	Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
		Pulley		Made in Koera
11	Accessories	Regulator		Made in China
		Glue water	3 Units	Made in Japan
		Absorber	8 Units	Made in China
12	Refrigeration		R134a	Consumer Provide
13	Weight of the Roo	f Mounting Units	220KG	

Bus Air-Condition System PAC22B1



10.		TERM	TECHNICAL SPECIFICATIONS	NOTES
	System Type		PAC22B 1	
2	Model		Roof Mounting / Used 2 Compressors	
3	Cooling Capacity		21000~22000Kcal/h	
4	Applications		10~11m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-22 24V X 2	PAERMA Compress
		Туре	Swash Plate	
		Displacement	214cc/rev X 2	
6	Compressors	Power Consumption	5KW X 2	
		Lubricant	ZXL 100PG 180ml X 2	
		Weight	9.5KG X 2 (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	6500m3/h	
		Number of Fans		Made in China / Mad in Japan
7	Condenser Unit	Filter Drier	3A Grade X 2	Made in China
		High Pressure Switch	OFF: 24.5kgf/cm2 , ON:17kgf/ cm2	Made in China
		Low Pressure Switch	OFF: 0.8kgf/cm2 , ON:2.2kgf/ cm2	
		Size (mm)		
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	4800 m3/h	
8	Evaporator Unit	Number of Blowers	6	
		Expansion Valve	3.0RT X 2	Japan Denso
		Weight		
		Size (mm)		
		Current Consumption	76A/24VDC	
		Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
		Pulley		Made in Koera
11	Accessories	Regulator		Made in China
		Glue water	4 Units	Made in Japan
		Absorber	12 Units	Made in China
12	Refrigeration		R134a	Consumer Provide
13	Weight of the Roc	f Mounting Units	240KG	

Bus Air-Condition System PAC28B1







NO.	7	ΓERM	TECHNICAL SPECIFICATIONS	NOTES
	System Type		PAC28B 1	
2	Model		Roof Mounting / Used 2 Compressors	
3	Cooling Capacity		26000~28000Kcal/h	
	Applications		10~11m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V X 2	PAERMA Compressor
		Туре	Swash Plate	
		Displacement	313.4cc/rev X 2	
6	Compressors	Power Consumption	7.5KW X 2	
		Lubricant	ZXL 100PG 600ml X 2	
		Weight	14.5KG X 2 (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	7400m3/h	
7	0	Number of Fans	4	Made in China / Made in Japan
7	Condenser Unit	Filter Drier	3A Grade X 2	Made in China
		High Pressure Switch	OFF: 24.5kgf/cm2 , ON:17kgf/ cm2	Made in China
		Low Pressure Switch Size (mm)	OFF: 0.8kgf/cm2 , ON:2.2kgf/ cm2	
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	6300 m3/h	
8	Evaporator Unit	Number of Blowers	6	
	.,	Expansion Valve	4.6RT X 2	Japan Denso
		Weight		
		Size (mm)		
		Current Consumption	115A/24VDC	
		Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
		Pulley		Made in Koera
11	Accessories	Regulator		Made in China
		Glue water	4 Units	Made in Japan
		Absorber	12 Units	Made in China
12	Refrigeration		R134a	Consumer Provide
13	Weight of the Roof Mounting Units		310KG	

Bus Air-Condition System PAC32B1







NO.	1	TERM	TECHNICAL SPECIFICATIONS	NOTES
1	System Type		PAC32B1	
2	Model		Roof Mounting / Used 2 Compressors	
3	Cooling Capacity		28000~32000Kcal/h	
	Applications		11~12m Bus	
5	Cooling Ability		Outside temperature is 35°C ,27°C CDB / 19.5°C CWB inside	
		Model	PLM-32 24V X 2	PAERMA Compressor
		Туре	Swash Plate	
		Displacement	313.4cc/rev X 2	
6	Compressors	Power Consumption	7.5KW X 2	
		Lubricant	ZXL 100PG 600ml X 2	
		Weight	14.5KG X 2 (With Clutch)	
		Radiator	Fin and tube coil (Inside screw pipe ordinary aluminum foil)	SUNJET Brand
		Air Flow	11100m3/h	
_	0 1 11 7	Number of Fans	6	Made in China / Made in Japan
7	Condenser Unit	Filter Drier	3A Grade X 2	Made in China
		High Pressure Switch	OFF: 24.5kgf/cm2 , ON:17kgf/ cm2	Made in China
		Low Pressure Switch	OFF: 0.8kgf/cm2, ON:2.2kgf/cm2	
		Size (mm)		
		Radiator	Fin and tube coil (Inside screw pipe Water-loving aluminum foil)	SUNJET Brand
		Air Flow	6300 m3/h	
8	Evaporator Unit	Number of Blowers	6	
	•	Expansion Valve	4.6RT X 2	Japan Denso
		Weight		
		Size (mm)		
		Current Consumption	115A/24VDC	
_	E	Thermo Start	Mainly Parts Import	Made in China
9	Electrical Control	Relay	Mainly Parts Import	Made in China
		Safety Switch	Mainly Parts Import	Made in China
		Electrical Wire	Mainly Parts Import	Made in China
10	Pipeline System		Air-Condition Pipe Line	Goodyear
		Waterspout	Waterspout of A/C System	Made in China
		Pulley		Made in Koera
11	Accessories	Regulator		Made in China
		Glue water	4 Units	Made in Japan
		Absorber	12 Units	Made in China
12	Refrigeration		R134a	Consumer Provide
13	Weight of the Roof Mounting Units		310KG	